

.308 Win., Hornady SST Interlock (165 grains), Tubal 7000

WARNING: Since we have no control over equipment or data which may be used with this program, no responsibility is implied or assumed for results obtained through its use. Input data and results may be incorrect or wrong. Therefore the use of this data for loading ammunition can cause serious injury to personnel and material. The computer-results had to be checked against data available in current loading manuals.

LOT-TO-LOT VARIATIONS OF POWDERS, PRIMER SUBSTITUTION AND COMPONENT CHANGE OFTEN RAISE PRESSURES TO UNSAFE LEVELS. THE USER MUST ASSUME THE ENTIRE RISK OF USING THIS DATA FOR LOADING PURPOSES.

QuickLOAD® V.3.6.05 #532889, © Copyright 1987-2011 - H.Broemel, Babenhausen, Germany

User Data:	Date: 30-ene-2014	Time: 21:32:06	File: 308 win 165 gr hornady sst interlock.dat		
Cartridge / Caliber	.308 Win.	Bullet	.308, 165, Hornady SST Inter		
Maximum Average Pressure, allowed	4150 bar	60191 psi. (Piezo CIP)	with boattail		
Groove Caliber	7,82 mm	0,308 in.	Bullet Weight	10,69 gm	165,0 gr.
Case Capacity, overflow	3,636 cm ³	56,0 gr. H2O	Bullet Length	32,26 mm	1,270 in.
Case Length	51,16 mm	2,014 in.	Bullet Seating Depth	13,56 mm	0,534 in.
Cartridge O.A. Length	69,85 mm	2,750 in.	Barrel/Tube Length	510,08 mm	20,0819 in.
Shot Start / Init Pressure	250,0 bar	3626 psi.	Cross Section Area of Bore	0,4751 cm ²	0,07364 in. ²

Propellant type	Tubal 7000				
Charge Weight	2,786 gm	43,0 gr.	Load Density	0,919 gm/cm ³	232,4 gr./in. ³
Heat of Explosion, Potential	3760 J/gm	243,6 J/gr.	Energy Density of Charge	3454 J/cm ³	56601 J/in. ³
Propellant Solid Density	1,62 gm/cm ³	409,68 gr./in. ³	Used Ratio of Specific Heats cp/cv	1,2403	
Burning Rate Factor Ba	0,515 1/s		Weighting Factor	0,5	
Burning Function Limit Z1	0,45		Prog.-/ Degressivity Factor a0	0,248	
Factor b	1,422		Bulk Density	0,915 gm/cm ³	231,4 gr./in. ³

Calculated and Estimated Data:					
Bullet Shank Seating Depth	8,48 mm	0,334 in.	Capacity Displaced by Seated Bullet	0,603 cm ³	0,0368 in. ³
Useable Case Capacity	3,033 cm ³	0,1851 in. ³	Bullet Travel at Muzzle Exit	472,48 mm	18,6 in.
Loading Ratio("Density") / Filling	100,4 % = compressed		Charge Fraction Burnt at Shot Start	1,30 %	

Predicted Data:					
Maximum Chamber Pressure	2714 bar	39369 psi.	Bullet Travel at Pmax	31,2 mm	1,23 in.
at Muzzle Exit:					
Bullet Velocity	701,4 m/s	2301 fps.	Pressure at Muzzle	538 bar	7797 psi.
Bullet Energy	2631 Joule	1940 ft.lbs.	Bullet Barrel Time	1,221 ms	
Propellant Burnt	85,7 %		Ballistic Efficiency	25,1 %	

Additional Data:				
Powder Lot		Primer Type and Lot	Federal 210	
Bullet Lot		Case Manufacturer	Lapua	
Measured Muzzle Vel., StdDev.		Measured Pressure, StdDev.		

Check Loading Manuals for Safe Minimum Charge Weight to Avoid Hazardous Ignition Conditions like Secondary Explosion Effects !
Real maximum (peak) of pressure is reached while bullet moves within barrel.
End of combustion occurs after the bullet's base passes muzzle.

