







Formulas

<p align="center">WIND - MIRAGE CHART</p>  <p>NO WIND 1-3 MPH 4-7 MPH 8-12 MPH</p>		<p align="center"><u>Wind Effects</u></p> <p>0-3 Hardly felt on face 3-5 Lightly felt on face 5-8 Tree leaves in motion 8-12 Raises dust and paper 12-15 Small trees sway 15-20 Larger trees sway</p>	<p align="center">Target Sz Inches x 27.77 Mil Reading of Target = YARDS</p>																															
<p>$\frac{\text{Angle}}{4} = \text{MPH}$ $\frac{60}{4} = 15$</p> 		<table border="1"> <thead> <tr> <th>Yards</th> <th>M/Yd</th> <th>Meters</th> </tr> </thead> <tbody> <tr> <td>1.0936</td> <td>1</td> <td>0.9144</td> </tr> <tr> <th>MIL</th> <th>MIL/MOA</th> <th>MOA</th> </tr> <tr> <td>1.00</td> <td>1</td> <td>3.438</td> </tr> </tbody> </table>	Yards	M/Yd	Meters	1.0936	1	0.9144	MIL	MIL/MOA	MOA	1.00	1	3.438	<p align="center">USMC (not to scale)</p> 																			
Yards	M/Yd	Meters																																
1.0936	1	0.9144																																
MIL	MIL/MOA	MOA																																
1.00	1	3.438																																
<p>Range (100s) x Velocity (mph) = MILS</p> <p align="center">Constant (7.62mm, 175gr @ 2600 fps)</p> <table border="1"> <tbody> <tr> <td>100 - 500 yds</td> <td>= 53</td> <td rowspan="6"> <p align="center"><u>Simple Method</u></p> <p>.25 mil per 100yds @10mph</p> </td> </tr> <tr> <td>600 yrd</td> <td>= 49</td> </tr> <tr> <td>700 - 800 yrds</td> <td>= 46</td> </tr> <tr> <td>900 yrds</td> <td>= 42</td> </tr> <tr> <td>1000 yrds</td> <td>= 39</td> </tr> </tbody> </table>		100 - 500 yds	= 53	<p align="center"><u>Simple Method</u></p> <p>.25 mil per 100yds @10mph</p>	600 yrd	= 49	700 - 800 yrds	= 46	900 yrds	= 42	1000 yrds	= 39	<p align="center"><u>Humidity Effects</u></p> <p>Humidity up = impact down Humidity down = impact up</p>	<p align="center">Slope Dope</p> <table border="1"> <thead> <tr> <th>Angle</th> <th>10°</th> <th>20°</th> <th>30°</th> <th>40°</th> <th>50°</th> <th>60°</th> <th>70°</th> <th>80°</th> <th>90°</th> </tr> </thead> <tbody> <tr> <td>COS</td> <td>.98</td> <td>.94</td> <td>.85</td> <td>.75</td> <td>.65</td> <td>.50</td> <td>.35</td> <td>.20</td> <td>.0</td> </tr> </tbody> </table>	Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°	COS	.98	.94	.85	.75	.65	.50	.35	.20	.0
100 - 500 yds	= 53	<p align="center"><u>Simple Method</u></p> <p>.25 mil per 100yds @10mph</p>																																
600 yrd	= 49																																	
700 - 800 yrds	= 46																																	
900 yrds	= 42																																	
1000 yrds	= 39																																	
Angle	10°		20°	30°	40°	50°	60°	70°	80°	90°																								
COS	.98	.94	.85	.75	.65	.50	.35	.20	.0																									
<p>Rule of Thumb: 20% = ~1moa affect on POI</p>		<p align="center"><u>Common Measurements</u></p> <p>Exterior Door = 36" x 80" 55gal Barrel = 12" x 15" 5gal Bucket = 12" x 8" Cinder Block = 8" x 2" License Plate = 12" x 6" Door Knob = 3"</p>																																

Formulas

<p align="center">WIND - MIRAGE CHART</p>  <p>NO WIND 1-3 MPH 4-7 MPH 8-12 MPH</p>		<p align="center"><u>Wind Effects</u></p> <p>0-3 Hardly felt on face 3-5 Lightly felt on face 5-8 Tree leaves in motion 8-12 Raises dust and paper 12-15 Small trees sway 15-20 Larger trees sway</p>	<p align="center">Target Sz Inches x 27.77 Mil Reading of Target = YARDS</p>																															
<p>$\frac{\text{Angle}}{4} = \text{MPH}$ $\frac{60}{4} = 15$</p> 		<table border="1"> <thead> <tr> <th>Yards</th> <th>M/Yd</th> <th>Meters</th> </tr> </thead> <tbody> <tr> <td>1.0936</td> <td>1</td> <td>0.9144</td> </tr> <tr> <th>MIL</th> <th>MIL/MOA</th> <th>MOA</th> </tr> <tr> <td>1.00</td> <td>1</td> <td>3.438</td> </tr> </tbody> </table>	Yards	M/Yd	Meters	1.0936	1	0.9144	MIL	MIL/MOA	MOA	1.00	1	3.438	<p align="center">USMC (not to scale)</p> 																			
Yards	M/Yd	Meters																																
1.0936	1	0.9144																																
MIL	MIL/MOA	MOA																																
1.00	1	3.438																																
<p>Range (100s) x Velocity (mph) = MILS</p> <p align="center">Constant (7.62mm, 175gr @ 2600 fps)</p> <table border="1"> <tbody> <tr> <td>100 - 500 yds</td> <td>= 53</td> <td rowspan="6"> <p align="center"><u>Simple Method</u></p> <p>.25 mil per 100yds @10mph</p> </td> </tr> <tr> <td>600 yrd</td> <td>= 49</td> </tr> <tr> <td>700 - 800 yrds</td> <td>= 46</td> </tr> <tr> <td>900 yrds</td> <td>= 42</td> </tr> <tr> <td>1000 yrds</td> <td>= 39</td> </tr> </tbody> </table>		100 - 500 yds	= 53	<p align="center"><u>Simple Method</u></p> <p>.25 mil per 100yds @10mph</p>	600 yrd	= 49	700 - 800 yrds	= 46	900 yrds	= 42	1000 yrds	= 39	<p align="center"><u>Humidity Effects</u></p> <p>Humidity up = impact down Humidity down = impact up</p>	<p align="center">Slope Dope</p> <table border="1"> <thead> <tr> <th>Angle</th> <th>10°</th> <th>20°</th> <th>30°</th> <th>40°</th> <th>50°</th> <th>60°</th> <th>70°</th> <th>80°</th> <th>90°</th> </tr> </thead> <tbody> <tr> <td>COS</td> <td>.98</td> <td>.94</td> <td>.85</td> <td>.75</td> <td>.65</td> <td>.50</td> <td>.35</td> <td>.20</td> <td>.0</td> </tr> </tbody> </table>	Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°	COS	.98	.94	.85	.75	.65	.50	.35	.20	.0
100 - 500 yds	= 53	<p align="center"><u>Simple Method</u></p> <p>.25 mil per 100yds @10mph</p>																																
600 yrd	= 49																																	
700 - 800 yrds	= 46																																	
900 yrds	= 42																																	
1000 yrds	= 39																																	
Angle	10°		20°	30°	40°	50°	60°	70°	80°	90°																								
COS	.98	.94	.85	.75	.65	.50	.35	.20	.0																									
<p>Rule of Thumb: 20% = ~1moa affect on POI</p>		<p align="center"><u>Common Measurements</u></p> <p>Exterior Door = 36" x 80" 55gal Barrel = 12" x 15" 5gal Bucket = 12" x 8" Cinder Block = 8" x 2" License Plate = 12" x 6" Door Knob = 3"</p>																																